



HEAVY DUTY NYLON* SLINGS


(Web Thickness is Approximately 3/16")



LOOP AND LOOP (LL) Flat Eye slings are popular slings which can be used in all three types of hitches. They are easier to remove from beneath the load after the load is in place.



LOOP AND LOOP (LL) Twisted Eye slings are similar to flat eye slings except the eyes are turned 90° to form a better choker hitch. This type of eye also nests together better when used in a basket hitch.



ENDLESS (ES) slings are versatile and the most economically priced. They can be used in all three types of hitches and the wear points can be moved to increase sling life. The sling legs can be spread for improved load balance.

ENDLESS

		EYE & EYE			
		RATED CAPACITIES IN LBS.			
	Flat Eye	Twisted Eye	Vertical	Choker	Basket
	(LL)	(LL)			
ONE PLY	LL1-801		1,800	1,250	3,200
	LL1-802		3,200	2,500	6,400
	LL1-803		4,800	3,800	9,600
	LL1-804		6,400	5,000	12,800
	LL1-805		8,000	6,400	16,000
	LL1-806		9,800	7,700	19,200
	LL1-808		12,800	10,200	25,600
	LL1-810		16,000	12,800	32,000
	LL1-812		18,200	15,400	38,400
TWO PLY	LL2-801		3,200	2,500	6,400
	LL2-802		6,400	5,000	12,800
	LL2-803		8,600	6,900	17,200
	LL2-804		11,500	9,200	23,000
	LL2-805		13,600	10,900	27,200
	LL2-806		16,300	13,000	32,600
	LL2-808		19,200	15,400	38,400
	LL2-810		22,400	17,900	44,800
	LL2-812		26,900	21,500	53,800
THREE PLY	LL3-801		4,100	3,300	8,200
	LL3-802		8,300	6,600	16,600
	LL3-803		12,500	10,000	25,000
	LL3-804		16,000	12,800	32,000
	LL3-805		19,200	15,400	38,400
	LL3-806		23,000	18,400	46,000
	LL3-808		30,700	24,500	61,400
	LL3-810		36,800	29,400	73,600
	LL3-812		44,000	35,200	88,000
FOUR PLY	LL4-801		5,000	4,000	10,000
	LL4-802		10,000	8,000	20,000
	LL4-803		14,900	11,900	29,800
	LL4-804		19,800	15,800	39,600
	LL4-805		24,800	19,800	49,600
	LL4-806		29,800	23,800	59,600
	LL4-808		39,700	31,700	79,400
	LL4-810		49,600	39,600	99,200
	LL4-812		59,500	47,600	119,000

NOTE: See Eye Length Chart Page 17.

CAUTION DO NOT EXCEED RATED CAPACITIES.

		RATED CAPACITIES IN LBS.		
		Vertical	Choker	Basket
ONE PLY	ES1-801	3,200	2,500	6,400
	ES1-802	6,400	5,000	12,800
	ES1-803	8,600	6,900	17,200
	ES1-804	11,500	9,200	23,000
	ES1-805	13,600	10,900	27,200
	ES1-806	16,300	13,000	32,600
	ES1-808	19,200	15,400	38,400
	ES1-810	22,400	17,900	44,800
	ES1-812	26,900	21,500	53,800
TWO PLY	ES2-801	6,200	4,900	12,400
	ES2-802	12,200	9,800	24,400
	ES2-803	16,300	13,000	32,600
	ES2-804	20,700	16,500	41,400
	ES2-805	24,500	19,600	49,000
	ES2-806	28,600	23,000	57,200
	ES2-808	30,700	24,500	61,400
	ES2-810	33,600	26,800	67,200
	ES2-812	37,600	30,000	75,200
THREE PLY	ES3-801	8,000	6,400	16,000
	ES3-802	16,000	12,800	32,000
	ES3-803	21,500	17,200	43,000
	ES3-804	28,700	23,000	57,400
	ES3-805	34,000	27,200	68,000
	ES3-806	40,700	32,500	81,400
	ES3-808	46,000	36,800	92,000
	ES3-810	51,500	41,200	103,000
	ES3-812	59,200	47,300	118,400
FOUR PLY	ES4-801	10,000	8,000	20,000
	ES4-802	19,800	15,800	39,600
	ES4-803	26,700	21,300	53,400
	ES4-804	35,600	28,400	71,200
	ES4-805	42,200	33,700	84,400
	ES4-806	50,500	40,400	101,000
	ES4-808	57,600	46,000	115,200
	ES4-810	67,200	53,700	134,400
	ES4-812	80,700	64,500	161,400

HOW TO ORDER:

Example:

1. Designate sling configuration, i.e. loop and loop (LL) or endless sling (ES)
Example: Endless sling.

ES

2. Designate number of plies (2) and heavy duty of web (8).
Example: Endless sling, 2 ply, heavy duty web.

ES2-8


3. Designate width of sling (inches and length of sling (feet)).
Example: Endless sling, 2 ply, heavy duty web, 4" wide, 12' long.

ES2 - 804 x 12'

* Polyester available upon request.


Add a "P" to end of sling code for Polyester.

NYLON* SLINGS with HARDWARE



CHOKER SLINGS (CS)

Are slings that have a triangle and choker fitting on either end. This is most commonly used in a choker hitch, but can also be used in basket and vertical hitches.



TRIANGLE SLINGS (TS)

Are slings that have a triangle fitting on each end. These are normally used in a basket hitch but can also be used in a vertical hitch. These slings are more economical than choker slings, but they cannot be used in a choker hitch.

STANDARD DUTY WEB

		RATED CAPACITIES IN LBS.			
		Vertical	Choker	Basket	
	(CS)	(TS)			
ONE PLY	CS1-602	TS1-602	2,400	1,900	4,800
	CS1-603	TS1-603	3,600	2,900	7,200
	CS1-604	TS1-604	4,800	3,800	9,600
	CS1-606	TS1-606	7,200	5,800	14,400
TWO PLY	CS2-602	TS2-602	4,800	3,800	9,600
	CS2-603	TS2-603	6,500	5,200	13,000
	CS2-604	TS2-604	8,600	6,900	17,200
	CS2-606	TS2-606	12,600	10,100	25,200

Triangle Slings can not be used in a choker hitch.

*Polyester Available upon request.

HOW TO ORDER:

1. Designate sling configuration, i.e. choker sling (CS) or triangle sling (TS)
Example: Choker sling.

2. Designate number of plies and heavy duty (8) or standard duty (6) web.
Example: Choker sling, 2 ply, heavy duty web.

3. Designate width of sling (inches and length of sling (feet).

Example: Choker sling, 2 ply, heavy duty web, 2" wide, 10' long.

Example:

CS

CS2-8

CS2 - 802 x 10'

HEAVY DUTY WEB

		RATED CAPACITIES IN LBS.			
		Vertical	Choker	Basket	
	(CS)	(TS)			
ONE PLY	CS1-802	TS1-802	3,200	2,500	6,400
	CS1-803	TS1-803	4,800	3,800	9,600
	CS1-804	TS1-804	6,400	5,000	12,800
	CS1-805	TS1-805	8,000	6,400	16,000
	CS1-806	TS1-806	9,600	7,700	19,200
	CS1-808	TS1-808	12,800	10,200	25,600
	CS1-810	TS1-810	16,000	12,800	32,000
	CS1-812	TS1-812	19,200	15,400	38,400
	CS1-816	TS1-816	25,500	20,400	51,000
	CS1-818	TS1-818	28,700	23,000	57,400
	CS1-820	TS1-820	38,400	30,700	76,600
	TWO PLY	CS2-802	TS2-802	6,400	5,000
CS2-803		TS2-803	8,600	6,900	17,200
CS2-804		TS2-804	11,500	9,200	23,000
CS2-805		TS2-805	14,000	11,200	28,000
CS2-806		TS2-806	16,800	13,400	33,600
CS2-808		TS2-808	22,400	17,900	44,800
CS2-810		TS2-810	28,000	22,400	56,000
CS2-812		TS2-812	33,600	26,800	67,200
CS2-816		TS2-816	44,800	35,800	89,800
CS2-818		TS2-818	50,400	40,300	100,800
CS2-820		TS2-820	56,000	44,800	112,000
CS2-824		TS2-824	67,200	53,700	134,400

Three and four ply hardware slings are available upon request.

Triangle Slings can not be used in a choker hitch.

CAUTION DO NOT EXCEED RATED CAPACITIES.

REVERSED LOOP SLINGS



REVERSED LOOP (RL)

Reversed Loop (RL) slings have protective webbing over the entire body and eyes. This extra webbing reinforces the sling and protects it from wear, resulting in an exceptionally strong and rugged sling.

Heavy Duty Webbing

	Code No.	Vertical	Choker	Basket	Width	Thickness	Eye Length
ONE PLY	RL1-802	4,500	3,600	9,000	2	5/16	9
	RL1-804	7,700	6,200	15,400	4	5/16	15
	RL1-808	11,000	8,800	22,000	6	5/16	15
TWO PLY	RL2-802	6,500	5,200	13,000	2	1/2	9
	RL2-804	13,000	10,400	26,000	4	1/2	15
	RL2-808	20,000	16,000	40,000	6	1/2	15
THREE PLY	RL3-804	16,400	13,100	32,800	4	11/16	15
	RL3-808	25,500	20,400	51,000	6	11/16	15
FOUR PLY	RL4-808	34,000	27,200	68,000	6	7/8	15

Standard Duty Webbing

	Code No.	Vertical	Choker	Basket	Width	Thickness	Eye Length
ONE PLY	RL1-602	3,600	2,900	7,200	2	1/4	9
	RL1-603 1/2	5,000	4,000	10,000	3-1/2	1/4	12
	RL1-604	6,800	5,400	13,600	4	1/4	15
	RL1-608	8,000	6,400	16,000	6	1/4	15
TWO PLY	RL2-602	5,200	4,200	10,400	2	3/8	9
	RL2-603 1/2	9,000	7,200	18,000	3-1/2	3/8	12
	RL2-604	10,500	8,400	21,000	4	3/8	15
	RL2-608	14,400	11,500	28,800	6	3/8	15
THREE PLY	RL3-603 1/2	12,000	9,800	24,000	3-1/2	1/2	12
	RL3-604	14,000	11,200	28,000	4	1/2	15
	RL3-608	20,000	16,000	40,000	6	1/2	15

WIDE BODY SLINGS (WBS)

Wide Body Slings (WBS) are basket hitch slings that distribute the load over a wide area and give good balance to extra large and heavy loads. They are constructed from an endless sling with the two lengths stitched side by side.

Body Width	Code Number	Vertical Basket Hitch Cap. In Lbs.	Eye Length	Eye Width
6"	WBS1-806	15,400	9"	1 1/2"
6"	WBS2-806	28,600	9"	1 1/2"
8"	WBS1-808	20,400	12"	2"
8"	WBS2-808	38,000	12"	2"
10"	WBS1-810	25,800	15"	2 1/2"
10"	WBS2-810	47,800	15"	2 1/2"
12"	WBS1-812	30,800	18"	2"
12"	WBS2-812	57,200	18"	3"
16"	WBS1-816	38,000	24"	2 3/4"
16"	WBS2-816	61,500	24"	4"
20"	WBS1-820	45,000	30"	3 1/2"
20"	WBS2-820	83,000	30"	5"
24"	WBS1-824	52,000	36"	4"
24"	WBS2-824	70,000	36"	6"

HOW TO ORDER:

1. Designate sling configuration, i.e. reversed loop (RL) or wide body sling with attached eyes (AES).
Example: Reversed Loop.

2. Designate number of plies and heavy duty (8) or standard duty (6) web.
Example: Reversed loop sling, 2 ply, heavy duty web.

3. Designate width of sling (inches and length of sling (feet)).
Example: Reversed loop sling, 2 ply, heavy duty web, 10" wide, 20' long.

Example:

RL

RL2-8

RL2 - 810 x 20'

ATTACHED EYE SLING (AES)

Attached-Eye Slings are to be used in basket hitch with light loads and wide bearing areas. The eyes are made from separate material to accommodate small crane hooks. These slings have one ply bodies and two ply eyes.

Body Width	Code Number	Vertical Basket Hitch Cap. In Lbs.	Eye Length	Eye Width
6"	AES1-806	3,000	10"	1"
6"	AES2-806	6,000	10"	1"
8"	AES1-808	3,000	10"	1"
8"	AES2-808	6,000	10"	1"
10"	AES1-810	3,000	12"	1"
10"	AES2-810	6,000	12"	1"
12"	AES1-812	3,000	12"	1"
12"	AES2-812	6,000	12"	1"
16"	AES1-816	5,000	12"	2"
16"	AES2-816	10,000	12"	2"
20"	AES1-820	5,000	18"	2"
20"	AES2-820	10,000	18"	2"
24"	AES1-824	5,000	18"	2"
24"	AES2-824	10,000	18"	2"

CAUTION DO NOT EXCEED RATED CAPACITIES.